

**STL(Z) 1550/.. G - 3,5 (3,81) - H - green**




**2-20 (16) poles, Spacing 3,5 mm or 3,81 mm  
insert required no. of poles ..**






**STLZ 1570/.. G - 3,81 - V - green**

**2-20 poles, Spacing 3,81 mm  
insert required no. of poles ..**

**Ratings:**

			
	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
Rated Voltage	300 V	300 V	160 V
Rated Current	8 A	8 A	9 A (T60)
Rating Impulse Voltage/Dirt Level			4 kV/3

**Ratings:**

			
	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
Rated Voltage	300 V	300 V	160 V
Rated Current	8 A	8 A	9 A (T60)
Rating Impulse Voltage/Dirt Level			4 kV/3

**Dimensions**

Spacing	3,5 mm (3,81 mm)
PCB Hole Diameter	1,2 mm

**Materials**

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Contact Pin	Cu

**Colour**

green	RAL 6018
-------	----------

**Dimensions**

Spacing	3,81 mm
PCB Hole Diameter	1,2 mm

**Materials**

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Contact Pin	Cu

**Colour**

green	RAL 6018
-------	----------